

### Product Description

Range : ( +50 ~ +600 )°C



### Applications

We offer best quality Dig. Dry Block Temperature Calibrator. Also known as EN-PDBC600 , these are further more highly appreciated for portability and very very light weight. The rugged features of these products makes them highly sought after in the petrochemical , pharmaceutical industries & calibration laboratories etc. Our Calibrators are used for testing thermometers , sensors & thermocouples ranging from ( +50 ~ +600 )°C. The total weight of these is 7.0 kg.

### Technical Specifications

<b>Model No.</b>	<b>EN-PDBC600</b>
Temperature Range	( +50 ~ +600 )°C
<b>Heating Block Specifications</b>	
Material	Brass
No. Of Heaters	4 Nos.
Block Immersion	120mm. Insertion
Pocket Diameter	30mm. Insertion
No. Of Pockets	Providing 3 Pockets with Different holes from 2.6mm. To 13mm. Dia.

*All product specifications are subject to change without prior notice.*

**Technical Specifications****Controller Specifications**

Type	Microprocessor Logic Controller
Display Range	( 0 ~ +650 )°C
Accuracy	±0.5°C
Resolution	0.1°C
Stability	±0.2°C or Less
Uniformity	±0.2°C
Units	°C
Stabilization Time	15 minutes
Displays	LCD

**Standard Specifications**

Heating Time	( Ambient To 600°C ) : 30 minutes ( Approx. )
Switch Test Facility	Provided
Power Supply	230V AC ± 2.5/50Hz.
Dimensions	( 150 X 240 X 340 )mm.
Weight	7 kgs.

*All product specifications are subject to change without prior notice.*